



Specifications Ledvance LED  
Downlight Biolux DN150 21W 2200lm  
60D - 927-965 Tunable White | 175mm  
- Cutout 160mm - Dali Dimmable -  
Best Colour Rendering

[View Product](#)

General Information

|                          |                                        |
|--------------------------|----------------------------------------|
| SKU                      | 249875                                 |
| EAN                      | 4099854140310                          |
| Manufacturer Code        | 4099854140310                          |
| Brand                    | Ledvance                               |
| Manufacturer Name        | BIOLUX HCL DL DN150 S 21W TW DALI LEDV |
| Any Lamp all-in warranty | 5 Years                                |
| Average Lifetime (h)     | 40000                                  |

Technical Information

|                             |                                      |
|-----------------------------|--------------------------------------|
| Technology                  | LED Integrated                       |
| Replaces (Watt)             | 2x36                                 |
| Wattage                     | 21W                                  |
| Voltage (V)                 | 220-240                              |
| Dimmable                    | Dimmable with Dali                   |
| Colour Code                 | 927 Extra Warm White, 965 Daylight   |
| Colour temperature (Kelvin) | 2700 Extra Warm White, 6500 Daylight |
| Colour Rendering (Ra)       | 90-99                                |
| Colour of Light             | White                                |
| Light colour options        | Tunable White                        |
| Beam Angle (degree)         | 60                                   |

|                          |                                |
|--------------------------|--------------------------------|
| Luminous Flux (Lumen)    | 2200lm                         |
| Luminous Efficacy (lm/W) | 105                            |
| Power factor             | >0.90                          |
| Unified Glare Rating     | < 19 - for offices and schools |
| Optical Cover            | Opal                           |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                    |
|------------------------|--------------------|
| Mounting Method        | Recessed           |
| IP-rating              | IP20               |
| Impact Protection (IK) | IK03 - 0.35 joule  |
| Operating Temperature  | -20 to +40         |
| Housing                | Aluminium          |
| Colour of the Fixture  | White              |
| Fixture Connection     | Screwless terminal |
| Series                 | BIOLUX             |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 99  |
| Diameter (mm) | 175 |

## Sensor Information

Type of sensor

### Why Any-lamp?

No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

